

Systemx® Deck Paint

Rejuvenate

Systemx® Deck Paint is formulated to provide a tough, durable, breathing film for the protection of previously painted, unpainted, or textured concrete pool decks and walking surfaces. Systemx paint will resist the effects of weather, water, abrasion, and pool chemicals. Available in a variety of flat finish colors, Systemx paint coordinates perfectly with other Mortex product colors and enhances the beauty of any walkway, deck or backyard pool area.

- Can be applied to a damp surface; in fact, water helps the paint cure. In extremely dry areas, the deck should be misted with cool water prior to painting.
- Acrylic polymer is extremely sun fast and resistant to the sun's UV rays.
- Acrylic polymer is tough and abrasion resistant.
- Rollable. Cleans up with soap and water.
- Can be applied two coats in one day, only two hours apart.



Almond



Tan



Taupe



Auburn



Peach



Rustic



Malt



Clay



Gold



Rose



Aqua



Grey

All colors shown are approximate

Kool Deck® Topping Color Match Chart

Paint	Kool Deck
Aqua	Aqua
Auburn	Mauve
Clay	Terra Cotta
Gold.	Aztec Gold
Grey.	Birch Grey
Peach	Coral Peach
Rose.	Rose Pink
Rustic	Sedona Tan
Tan	Sand Buff
Taupe	T-5



Coverage
Bare surfaces: 125-150 ft ² gal.
Recoats: 250-300 ft ² gal.
Contents
Case: 1 gallon units
Weight
10 lbs. (4.5kg)
Shipping Info
freight truck, ocean or air



Mortex Manufacturing Co., Inc.
 1818 W. Price Street
 Tucson, AZ 85705-2217
 USA

Toll-Free: 800.338.3225
 Phone: 520.887.2631
 Fax: 520.293.8884

www.mortex.com

System[®] Deck Paint Instructions



Necessary Tools

- 3/4 inch Nap Rollers
- Paint Brushes for detailing
- High Pressure Washer
- Mortex Commercial Cleaner or Dishwashing Detergent

Optional Tools

- Mechanical Mixer (this can be a paddle attachment to a power drill)
- 5 gallon buckets

Coverage

- **125 – 150 sq. ft. on bare, sandblasted, or rough surfaces**
- **250 – 300 sq. ft. on recoats**

Coverage and the number of coats will vary depending on porosity and texture of surface. Care should be taken not to apply too much paint. Applying too much paint will require longer drying times prior to allowing traffic. Thinning is not required.

Surface Preparation

The keys to a successful System Deck Paint job are proper **Surface Preparation and Correct Application**. By following these simple steps, you're ensuring a virtually maintenance-free paint surface on your pool, walkway or deck.

- Step 1** The area to be painted should be tested for integrity and soundness. Water blast the surface to remove any loose paint or dirt.
- Step 2** Scrub the entire deck with dishwashing detergent or Mortex Commercial Cleaner. The deck should be completely free of dirt, oils, loose or peeling paint and chalk.
- Step 3** High pressure wash the surface.
- Step 4** Allow the deck to dry completely. In extremely dry areas the deck can be slightly damp, but with no puddles.

Mixing the Paint

System Deck Paint is self-priming; no other type of primer is recommended or should be used. Mechanically mix the paint to achieve uniform consistency and color. If you are using more than one (1) gallon of paint at a time, remember to box (intermix) several gallons together.

- Step 5** Use not more than a 3/4" nap roller. Apply at the recommended coverage rate. Ideal air temperatures for application are between 50-85° F. Surface temperature should be at least 50° F.

Do not paint when rain is imminent.

Note: Application temperature is between 50-85° F. Not intended for an immersion surface or in areas subject to vehicular traffic. Not recommended for wood decks. New concrete must be cured a minimum of 28 days.

The manufacturer offers this product and Information in good faith, but without guarantee either expressed or implied, as conditions and methods of use of our product are beyond our control.